

56 Frame Pool & Spa Motors

Switchless Design, 6.5" Frame Diameter, Category "S" & "J"



FEATURES:

- Two Compartment
- Shaft Threads - 7/16-20 UNF-2A
- 50°C Ambient
- Triple Bearing Protection
- 1081 Design
- Continuous Duty
- Class B Insulated
- Open Dripproof
- Sealed Ball Bearings
- 303 Stainless Steel Shaft
- Switchless Design
- Thermally Protected
- Discount Symbol: DS-FPS

extreme E Square Flange, Premium Energy Efficient, Full Service Factor, Full Rated

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List	Motor Frame	Length Less Shaft	Ship Wt. (lbs)
3/4 / 1/8	1.67	3450/1725	230	60	5.8/1.2	*EB2980	\$433	56Y	12.05	30
1.0 / 0.16	1.65	3450/1725	230	60	7.4/1.3	*EB2982	\$445	56Y	12.30	32
1 1/2 / 1/4	1.47	3450/1725	230	60	9.2/2.1	*EB2983	\$507	56Y	12.55	34
2 / 1/3	1.30	3450/1725	230	60	10.6/2.4	*EB2984	\$618	56Y	13.30	37

extreme E C-Flange, Premium Energy Efficient, Full Service Factor, Full Rated, Category "J"

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List	Motor Frame	Length Less Shaft	Ship Wt. (lbs)
3/4 / 1/10	1.50	3450/1725	230	60	5.6/1.2	*EB2973H	\$431	56J	12.27	21
1 / 1/8	1.40	3450/1725	230	60	6.5/1.3	*EB2975	\$443	56J	12.27	28
1 1/2 / 1/5	1.30	3450/1725	230	60	8.2/2.0	*EB2977	\$505	56J	12.27	32
2 / 1/4	1.20	3450/1725	230	60	10.0/2.1	*EB2979	\$616	56J	12.52	23

*Meets California Energy Commission Appliance Regulations 2008
(Publication Number CEC-400-2006-002-REV1)

Catalog numbers are for competitive comparison purposes only

extreme E EXTREME E® represents our most efficient running, highest performing lines of motors.

† All marks shown within this document are properties of their respective owners.