



CUSTOMER :

DELIVERY ADDRESS :

EMAIL TO : SALES@POOLSUPPLYUNLIMITED.COM

## COMMERCIAL MODEL SIZING INFORMATION FORM

1 POOL SIZE? (GALLONS) (CUBIC METERS) (LITROS) POOL COOLER MODEL :

---

2 DISTANCE FROM POOL PUMP TO CHILLER(S) INSTALLATION SITE ? (FEET) (METERS)

---

3 SURGE TANK ON SITE? YES / NO IF YES, FT.

4 CHILLER(S) FIT OUTDOOR EQUIPMENT AREA? YES / NO PIPE SIZE ON PROPERTY? : CIRCLE ONE  
2" / 2.5" / 3" / 4" / 6" / 8" /

IS THERE OUTSIDE AIR FLOW INTO AREA WITH CHILLER(S)? YES / NO

CIRCLE ONE : PARTIAL INDOOR-OUTDOOR AREA / OUTSIDE AREA

---

5 YES / NO

6 IF NO? CIRCLE ONE : ABOVE / BELOW GROUND LEVEL HOW MANY (FT./MTRS) FROM POOL PUMP?

---

7 DO THEY HAVE 3-PHASE ELECTRIC POWER AVAILABILITY?\*

YES  NO

WHAT IS THE POWER VOLTAGE?

CIRCLE ONE: 208 / 230 440 / 460 / 480

ELECTRICAL RUN FROM PANEL? FT. CIRCLE : 50 Hertz / 60 Hertz

\* CHILLER(S) will not operate and cannot be installed inside equipment rooms

\* THE GPC-23 TO GPC-220 MODELS ARE AVAILABLE IN SINGLE PHASE.

\*THE GPC-230 TO GPC- 2100 MODELS ARE 3-PHASE ONLY. \* 3-PHASE TO SINGLE PHASE REDUCER POWER TRANSFORMER ARE AVAILABLE.

