

CHEM LINK

Construction & Maintenance

Telephone: 800-826-1681

Fax: 269-679-4448

353 E. Lyons Street

Schoolcraft, MI 49087

www.chemlink.com

Last Revision: 02/02/17

Document No. DS1239

Product Description

NovaLink SL Pool Deck Joint Sealant is a self-leveling, moisture curing sealant, designed for application on horizontal joints in concrete construction such as driveways, sidewalks, balconies, stairwells and surrounding fountains and swimming pools. **NovaLink SL Pool Deck Joint Sealant** cures rapidly to a solid rubber seal that can accommodate 25% joint movement. Its unique polyether cure chemistry allows **NovaLink SL Pool Deck Joint Sealant** to be installed on damp concrete or in damp weather conditions without "outgassing" or forming CO₂ bubbles, as urethane sealants often do. Its excellent self leveling properties and smooth finish allow **NovaLink SL Pool Deck Joint Sealant** to be installed without tooling. The elimination of masking tape and tooling results in a significant reduction in labor. **NovaLink SL Pool Deck Joint Sealant** is solvent free and will not shrink. Its excellent adhesion to clean masonry or concrete allows it to be installed without a primer in most joints smaller than 1/2 inch wide.

Applicable Performance Standards

- ASTM C920, Type S, Grade P, Class 25, Uses T₂, M, & O
- Federal Specification TT-S-00230-C Type I, Class B
- Corps of Engineers CRD-C-541, Type I, Class B
- Canadian Standards Board CAN 19, 13-M82

Regulatory Compliance

- Conforms to OTC Rule for Sealants
- Meets requirements of California Regs: CARB and SCAQMD
- This product does not contain cancer causing chemicals listed in California Proposition 65.
- Conforms to USDA Requirements for Non-food Contact



Advantages

- Solvent free, 100% solids will not shrink
- 30 minute skin over
- No outgassing on damp surfaces
- Color stability, will not suntan
- Paintable within 24 hours (See limitations)
- +/- 25% joint movement

Colors

Stone, Gray, Black & Charcoal Gray

* Color matching is available in batch quantity only

Packaging

- 68 oz (2011ml) Pouch
4 pouches/carton, 45 cartons/pallet
- 2 and 5 gallon pails, 20 oz sausages or
50 gallon drums available by special order only.

Green Standards:

- LEED 2.2 for New Construction and Major Renovations: Low Emitting Materials (Section 4.1) 1 Point
- NAHB Model Green Home Building Guidelines: 5 Global Impact Points
- VOC Content: less than 16 grams / liter ASTM D2369 EPA Method 24 (tested at 240°F / 115°C)