

ADJUSTABLE IN-LINE SPRING CHECK VALVE

MADE OF PVC TYPE I MATERIAL
STAINLESS STEEL SPRING, BOLT, & WASHER
EPDM O-RING
NEOPRENE WASHER

RATED @ 150 PSI STATIC PRESSURE @ 72°F
MOLDED IN THE USA

ADJUSTING NUT 1 TURN = 1 PSI
FACTORY SET AT 5#

IPS—IRON PIPE SIZE (SAME AS SCH. 40)
FPT—FEMALE PIPE THREAD
MPT—MALE PIPE THREAD

PART NUMBER	COLOR	LENGTH	WEIGHT (LBS)	IPS CONNECTION
CV-0500-MF	GRAY	2.65	0.10	1/2" MPT X 1/2" FPT
UCV-0500-MF	PURPLE			
CV-0750-MF	GRAY	2.82	0.12	3/4" MPT X 3/4" FPT
UCV-0750-MF	PURPLE			
WCV-0750-MF	WHITE	2.89	0.15	1" MPT X 1" FPT
CV-1000-MF	GRAY			
WCV-1000-MF	WHITE			

INLET

OUTLET



PART NUMBER	COLOR	LENGTH	WEIGHT (LBS)	IPS CONNECTION
CV-0500-FF	GRAY	2.65	0.10	1/2" FPT X 1/2" FPT
UCV-0500-FF	PURPLE			
CV-0750-FF	GRAY	3.02	0.12	3/4" FPT X 3/4" FPT
UCV-0750-FF	PURPLE			
CV-1000-FF	GRAY	3.03	0.20	1" FPT X 1" FPT
UCV-1000-FF	PURPLE			

INLET

OUTLET



PART NUMBER	COLOR	LENGTH	WEIGHT (LBS)	IPS CONNECTION
CV-0500-FM	GRAY	2.57	0.10	1/2" FPT X 1/2" MPT
CV-0500-RB	GRAY	3.77	0.15	
CV-0575-FM	GRAY	2.57	0.12	1/2" FPT X 3/4" MPT
CV-0750-FM	GRAY	2.83	0.12	3/4" FPT X 3/4" MPT
CV-1000-FM	GRAY	2.99	0.15	1" FPT X 1" MPT

INLET

OUTLET

