



GV200 Series


GV200 Series Forged NON POTABLE Brass Gate Valve

Features:

- Constructed of heavy duty forged non potable brass.
- **Die-cast** body, **forged** bonnet are connected with a PTFE body to bonnet gasket for a leak proof seat.
- Screwed bonnet, non-rising stem, solid wedge disc and integral seats.
- Graphite stem seal packing.
- Cast iron hand wheel
- Rated at **200 PSI WOG; 125 PSI SWP** (working pressure, non shock)
- Threaded ends produced to ANSI/ASME B1.20.1 (NPT) standards.
- Sweat ends produced to ANSI B16.18-1984 standards
- Imported



MATERIAL SPECIFICATIONS	
Wheel Nut	Stainless Steel
Hand Wheel	Gray Iron
Packing Nut	Brass
Gland Follower	Brass
Stem Seal Packing	Graphite
Bonnet	Brass
Body-Bonnet Gasket	PTFE
Lock Nut	Brass
Stem	Brass
Disc	Brass
Body	Brass

DIMENSIONS (IN.)	SIZE	A (IPS)	A (Cx C)	B (IPS)	B (Cx C)	C	d
	1/2"	1.68	1.76	2.80	2.79	2.17	.51
	3/4"	1.76	2.34	2.99	3.10	2.17	.67
	1"	1.97	2.69	3.45	3.63	2.36	.83
	1 1/4"	2.30	3.01	4.06	4.37	2.84	1.07
	1 1/2"	2.46	3.36	4.47	4.96	2.84	1.34
	2"	2.69	3.98	5.26	6.13	3.15	1.77
	2 1/2"	3.43		6.44		3.94	2.21
	3"	3.71		7.48		4.33	2.68
	4"	4.45		9.25		5.12	3.55

Threaded Part Number	Sweat Part Number	Size	Ctn/Case Qty	List Price
GV200-50T		1/2"	10 / 100	\$ 29.35
	GV200-50S	1/2"	10 / 100	20.59
GV200-75T		3/4"	10 / 100	31.18
	GV200-75S	3/4"	10 / 100	21.89
GV200-100T		1"	5 / 50	43.28
	GV200-100S	1"	5 / 50	26.08
GV200-125T		1 1/4"	5 / 50	66.02
	GV200-125S	1 1/4"	5 / 50	40.39
GV200-150T		1 1/2"	2 / 30	100.08
	GV200-150S	1 1/2"	2 / 30	58.50
GV200-200T		2"	2 / 20	127.76
	GV200-200S	2"	2 / 20	109.54
GV200-250T		2 1/2"	1 / 10	290.69
GV200-300T		3"	1 / 10	405.19
GV200-400T		4"	1 / 4	705.02