



PVC Sch 80 Union Features:


- Ideal for swimming pool, spa and plumbing installations.
- EPDM O-Ring seal.
- Working pressure: 150 PSI at 72°F, 100 PSI at 120°F.
- Meets ASTM standards for Schedule 80 construction.
- Manufactured for AGI in an ISO 9002 facility.
- NSF listed.
- Available white or gray.
- **Third party certified NSF/ANSI 61&372.**

MATERIAL SPECIFICATIONS

Body	PVC
End Connector	PVC
Union Nut	PVC
O-Ring	EPDM

ISO 9002



DIMENSIONS (IN.)	SIZE	d3	D1	D2	L
	1/2"	.51	1.21	1.80	2.11
	3/4"	.71	1.45	2.15	2.42
	1"	.92	1.76	2.58	2.69
	1 1/4"	1.17	2.11	3.20	3.32
	1 1/2"	1.52	2.54	3.83	3.40
	2"	1.92	3.05	4.68	3.71
	3"	2.84	3.52	6.10	4.96
	4"	3.94	4.52	8.86	6.30

Part Number			IPS Size	Ctn Qty	List Price		
SCHEDULE 80 - WHITE					PV797	PV798	PV799
SLIP X SLIP	FIPT X FIPT	SLIP X FIPT			SXS	TXT	SXT
PV797-1/2	PV798-1/2		1/2"	36	\$ 5.17	\$ 5.42	
PV797-3/4	PV798-3/4		3/4"	24/144	6.81	7.07	
PV797-1	PV798-1		1"	12/96	8.76	9.36	
PV797-1 1/4	PV798-1 1/4		1 1/4"	12/96	15.58	16.42	
PV797-1 1/2	PV798-1 1/2	PV799-1 1/2	1 1/2"	8/64	19.69	20.48	\$ 20.04
PV797-2	PV798-2		2"	4/48	27.40	28.81	
SCHEDULE 80 - GRAY					PV697	PV698	
slip x slip	FIPT x FIPT				SxS	TXT	
PV697-1/2	PV698-1/2		1/2"	36/288	\$ 5.17	\$ 5.45	
PV697-3/4	PV698-3/4		3/4"	24/144	6.83	7.21	
PV697-1	PV698-1		1"	12/96	8.76	9.55	
PV697-1 1/4	PV698-1 1/4		1 1/4"	12/96	15.58	16.20	
PV697-1 1/2	PV698-1 1/2		1 1/2"	8/64	19.69	20.88	
PV697-2	PV698-2		2"	4/48	27.92	29.35	
PV697-3	PV698-3		3"	2/12	48.77	50.44	
PV697-4			4"	1/4	108.26		

Replacement O-Ring for PV797, PV798, PV799, PV697, PV698

PV796-1/2	1/2"	1	\$ 0.43
PV796-3/4	3/4"	1	0.43
PV796-1	1"	1	0.52
PV796-1 1/4	1 1/4"	1	0.52
PV796-1 1/2	1 1/2"	1	0.86
PV796-2	2"	1	0.86

Union Repair Split Nut

SNR150	1 1/2" FBT Repair Split Nut w/ Screw	125	7.60
SNR200	2" FBT REpair Split Nut w/ Screw	100	8.37

