

UNDERWATER LIGHTS

This superb collection of underwater lights includes the ultra-thin, 500W Slimlite and the new Slimlite 5G LED light which uses less energy. All lights are bronze and copper construction with chrome-plated reflector shells and grille has protective cast bronze powder coating. The 110-volt lights come with a protective grille. Each light is rigidly inspected and submersion tested for water tightness and performance. All lights come with halogen bulbs.

All lights are UL listed, when used with our niches. Lights and niches are designed for use in fresh water only. Niches have a 3/4" or a 1" threaded connection for installation in concrete or vinyl pools, and should be ordered separately.

SLIMLITE 5G/500 WATT EQUIVALENT

Energy efficient Slimlite 5G LED light utilizes up to 86% less energy than comparable incandescent lights. This is a direct replacement for existing standard 500W Slimlite. The light has superior lens geometry and innovative reflector design combined to create a wider beam and more uniform light distribution.

30' cord I.D. No. 56400
 50' cord I.D. No. 56401
 100' cord I.D. No. 56402
 150' cord I.D. No. 56403
 200' cord I.D. No. 56404
[Spec Sheet SS-UL 80.50](#)

NEW



NICHES FOR 500 WATT SLIMLITE

Model	Concrete	
	3/4"	1"
500w	56503	56504

SLIMLITE/110V-500 WATT

10" diameter and only 3-1/2" deep, designed for fresh water, concrete pools. Installs in any wall without haunching the concrete, simplifying installation and construction. Dual bulb is wired parallel: one bulb stays lit even if the other burns out. Uses (2) 250-watt, double tungsten halogen bulbs with an average life rating of 2000 hours and 5000 initial lumens. All lights are UL listed. Various cord lengths available.

13' cord I.D. No. 56301
 26' cord I.D. No. 56302 (standard)
 50' cord I.D. No. 56303-50
 75' cord I.D. No. 56303-75
[Custom Cord Length](#) I.D. No. 56303

LIGHTS

[Spec Sheet UL 80.20](#)

NICHES

[Spec Sheet UL 80.50](#)

REPLACEMENT BULB

I.D. No. 56811

UNDERWATER SPEAKERS

Sealed speaker for an underwater communication system between coach and swimmers, for providing background music for synchronized swimming and for scuba instruction. One speaker required for each 900 sq. ft. of pool surface area in deep water and one per 1200 sq. ft. in shallow area. Speakers are installed flush in niches within the pool wall and are covered by a protective grille. UL listed and recommended for use with Paragon niche.

UW30 UNDERWATER LOUD SPEAKER

A single 30-watt speaker adequately covers a 30' x 30' pool. Encased in blue high-impact ABS cover and sealed for underwater use to a depth of up to 10 feet.

(Niche and grill sold separately).

50' cord I.D. No. 68101-1
[Spec Sheet US 20.30](#)

NICHE FOR UW30 SPEAKER

Heavy-duty, cast bronze construction with 3/4" IPS threaded connection. Includes mounting hardware. Recommended mounting location is up to 4 feet below surface of the water and flush with the pool wall.

I.D. No. 68102

STAINLESS STEEL GRILLE

Mounts flush with pool wall.

I.D. No. 68103SS

[Spec Sheet US 80.07](#)

